

© 2017 All rights reserved

Author Affiliation

- Sami Asmar, Stephan Esterhuizen, Chad Edwards: NASA's Jet Propulsion Laboratory, California Institute of Technology, USA
- Yashwant Gupta: Giant Metrewave Radio Telescope, India
- Kishalay De: California Institute of Technology, USA
- Daniel Firre: European Space Operations Center, Germany
- Özgur Karatekin: Royal Observatory of Belgium
- Francesca Ferri: Università degli Studi di Padova, Centro di Ateneo di Studi e Attività Spaziali "Giuseppe Colombo," Italy

Motivation

- ESA's ExoMars Trace Gas Orbiter released Schiaparelli last October
- Giant Metrewave Radio Telescope recorded UHF signal during EDL
- Made available the only near real-time visibility of status at mission operations center
- During latter stage of sequence, anomaly resulted in loss of the lander, which was first observed and reported via the loss of the UHF signal at GMRT

Accomplishment

- Data acquired in Direct-to-Earth effort useful for reconstructing events, especially when combined with carrier signal received by TGO, Mars Express, and telemetry from on-board sensors
- Understanding the probe's state and trajectory
- Contribute understanding Mars's atmosphere in cooperation with the Atmospheric Mars Entry and Landing Investigations & Analysis (AMELIA) team. AMELIA aims include studying the major properties of Martian atmosphere, such as density, pressure, temperature and wind

GMRT

- GMRT is an array of thirty 45-m antennas operated by the National Centre for Radio Astrophysics
- A sub-array of 12 of the antennas was utilized during EDL event, an effective collecting area equivalent to a single 156-m diameter antenna
- For separation, 16 antennas were utilized
- Signal level too low to recover Schiaparelli data stream
- Objective was by design detecting the lander's residual carrier signal,
 which was predicted to be just a few dB above noise floor

ExoMars/Schiaparelli/EDM Entry, Descent, Landing (EDL) Detection at GMRT, India 2016-10-19

Spectrogram Frequency (Hz) vs. Time (s)





Figure shows the observed Schiaparelli carrier frequency, after removal of an a priori model based on the predicted lander trajectory. This information was made available via Internet from GMRT to ESOC during the landing event. The GMRT analysis provided confirmation of the aliveness of the lander through entry, peak heating, and subsequent parachute deployment. At 14:57:08 UTC Earth Receive Time, the signal was unexpectedly lost. This epoch corresponds to a Spacecraft Event Time (SCET) of 14:47:21, well in advance of the predicted touchdown time of 14:48:33

14:57:50 : Predicted Backshell & Parachute Jetison


(This exposes + 6 dBiC antenna), Thrusters On

14:58:20 : Predicted Thursters O 8 Touchdown

TGO/EDM Separation Event UHF Detected at GMRT, India 2016-10-16



GMRT Doppler & Elevation Profiles



UHF DTE Link Performance

- Initially assume 25 dishes for link analysis:
 - Effective Area: 19,880 m² (25 dishes, 45m, 50% efficiency)
 - Expected Pc/No: 17.2 dB-Hz (+6 dBiC) to 1.3 dB-Hz (-10 dBiC)
 - Depending on EDM antenna pattern
- Spacecraft-Earth range at arrival ~ 1.16 AU
- Frequency = 401.585 MHz; transmitted power = 5 W
- System Temperature = 106K (Mars ~10 degrees off galactic plane)
- Target sensitivity at GMRT ~3 dB-Hz

Communications Methods – 1 of 3 Relay Via Mars Orbiter

An orbiter overhead receives UHF signal from lander

Relays telemetry to DSN





Figure 2. The Doppler profile of the EDL sequence of the Phoenix mission as captured and relayed through the MRO spacecraft in 2008.

Communications Methods – 2 of 3 Direct to Earth Eavesdropping

 In the absence of sufficient link budget for telemetry, the Doppler profile received at Earth reveals very important information


Curiosity UHF Doppler profile received at Parkes Radio

Telescope in 2012



Communications Methods – 3 of 3 Introducing MarCO

- CubeSats have not flown in deep space yet
- Fly CubeSat with the mission to watch EDL event and relay data to DSN





Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not constitute or imply its endorsement by the United States Government or the Jet Propulsion Laboratory, California Institute of Technology.

Copyright 2017. All rights reserved.